

# VT275

TRACK LOADER

GEHL®



## KEY FEATURES

- **NEW** Color Display with Keyless Start + Security Code
- IdealTrax™ Auto Tensioning System
- **NEW** Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- Auxiliary Hydraulics with Drain Case
- **NEW** LED Work, LED Rear Lights + Egress Lighting
- Vertical Lift Arm for More Reach at Dump Height
- **NOW STANDARD** Hydraglide™ Ride Control
- **NEW** Dual Flange Idlers - Front + Rear
- **NOW STANDARD** Pilot Joystick Controls
- **NOW STANDARD** Backup Alarm

# VT275 TRACK LOADER



## SPECIFICATIONS

	IMPERIAL	METRIC	
WEIGHT + DIMENSIONS	Operating Weight	10051 lbs	4559 kg
	Overall Operating Height - Fully Raised	167.9"	4265 mm
	Height to Hinge Pin - Fully Raised	129.5"	3289 mm
	Overall Height to Top of ROPS	82"	2082 mm
	Dump Angle at Full Height		42°
	Dump Height - Fully Raised	98.5"	2502 mm
	Rollback Angle Fully Raised		92°
	Overall Length with Bucket	150"	3810 mm
	Dump Reach at Full Height	34.6"	879 mm
	Rollback Angle at Ground		29°
	Seat to Ground Height	39.5"	1003 mm
	Crawler Base	64.3"	1633 mm
	Overall Width - Less Bucket	71"	1803 mm
	Ground Clearance to Chassis	9"	229 mm
	Overall Length without Bucket	119"	3023 mm
	Specified Height	89"	2261 mm
	Reach at Specified Height	54.4"	1382 mm
	Departure Angle		30°
	Clearance Radius - Front with Bucket	93"	2362 mm
	Clearance Radius - Front without Bucket	58.5"	1486 mm
Clearance Radius - Rear	69"	1753 mm	
Bucket Width	74"	1880 mm	
Standard Track Width	15.7"	400 mm	
CAPACITIES	Operating Capacity at 35% Tipping Load	2750 lbs	1247 kg
	Operating Capacity at 35% Tipping Load with Side Weights	2870 lbs	1302 kg
	Operating Capacity at 50% Tipping Load	3929 lbs	1782 kg
	Operating Capacity at 50% Tipping Load with Optional Side Weights	4100 lbs	1860 kg
ENGINE	Make / Model	Yanmar / 4TNV98CT-XNGL	
	Type	Tier 4	
	Gross Power	72 HP	53.7 kW
	Net Power	70.7 HP	52.7 kW
	Maximum Torque @ 1800 rpm	217 ft/lbs	294 Nm
Battery	12 V	3.0 kW	
PERFORMANCES	Travel Speed	5.5 mph	8.9 km/hr
	Travel Speed with 2-Speed Option	8.4 mph	13.5 km/hr
	Tractive Effort	10789 lbs	4894 kg

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.

## STANDARD FEATURES

- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Back-Up Alarm
- NEW Battery Disconnect
- Brake Control (Auto/Manual)
- NEW Color Display with Keyless Start + Security Code
- NEW Dual Flange Idlers - Front + Rear
- NEW Egress Lighting with Time Delay
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- High-Back Adjustable Seats
- IdealTrax™ Auto Tensioning System
- Flip-Up Cooler
- Foot Throttle / NEW Deceleration Pedal
- Hand Throttle
- Horn
- Hydraloc™ Safety System
- Hydraglide™ Ride Control
- NEW Hydraulic Variable Speed Fan
- Hydrostatic Drive - Servo
- Integral Access Plate (removable)
- NEW LED Tail + Work Lights
- NEW Lift Arm Shape for Improved Visibility
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Operated Joystick Controls
- ROPS/FOPS Level II Overhead Guard
- 12-Volt + USB Charging Ports
- Two Speed Drive
- Sloped Roof
- Greasable Pins
- Manual Attach

## OPTIONAL FEATURES

- 14-Pin Attachment System
- Air Conditioning in Cab Enclosure
- Back-Up Alarm
- Bluetooth Hands-Free Radio
- Cab Enclosure
- Cast Rear Bumper
- Side Counterweights
- NEW Creep Mode Adjustable
- Door Options: Swing-Out, Fold-Up or Impact
- Engine Pre-Cleaner
- High-Flow Auxiliary Hydraulics
- Hydraulic Power-A-Tach® Attachment Mounting System
- NEW Impact Side Windows
- NEW LED Road Light Package
- NEW LED Side Lights
- FOPS Level II with Light Guard
- Rearview Camera
- Rearview Mirror
- NEW Reversible Cooling Fan
- Selectable Self-Leveling Hydraulic Lift Action
- Sound Reduction Package
- Suspension Seat - Air Ride or Mechanical
- NEW Cloth, Heated Seat with Air Suspension and Extended Backrest
- 4-Way Flashers
- Sliding Side Windows
- 4-Point Lift



West Bend, WI 53095 U.S.A. | Tel: 262-334-9461 | Fax: 262-338-7517